

Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W

TRIAC Dimmable Driver Series 200W

Series: TRIAC-12VIP66-200W | TRIAC-24VIP66-200W | TRIAC-48VIP66-200W



Features

Output:	Constant Voltage
Range:	200-240VAC
PFC design:	Built-in active PFC function
Efficiency:	Up to 88%
Protections:	Short circuit/ over load/ over temperature
Heat dissipation:	Cooling by free air convection
Waterproof performance:	IP66
Dimming function:	<u>Phase dimming</u> : work with leading edge, and trailing edge, TRIAC dimmers.
Dimming range:	0-100%
Application:	Suitable for the application of LED lighting
Warranty:	5 years warranty




Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W

Specification


Model		TRIAC-12VIP66-200W		TRIAC-24VIP66-200W	TRIAC-48VIP66-200W
Certificate		ENEC / TUV / SAA(GMA certificate) / CB / CCC / CE / SELV / RoHS / Reach			
Output	DC Voltage	12V	24V	48V	
	Voltage Tolerance	±0.5V			
	Voltage Regulation	≤0.5%			
	Rated current	16.66A	8.33A	4.16A	
	Rated power	200W			
	Load Regulation	≤2%	≤1%		
Input	Voltage Range	200-240VAC			
	Frequency Range	47 - 63Hz			
	THD(Typ.) @ full load	≤20%@200VAC @230VAC @240VAC			
	Efficiency @ full load	85%@230VAC	87%@230VAC	88%@230VAC	
	AC Current (Max.)	1.3A			
	Inrush Current (Typ.)	96A, 72us@230VAC	96A, 72us@230VAC	72.8A,132us@50%Ipeak	
	Leakage current	<0.5mA			
Protection	Short Circuit	Hiccup mode, re-power on to recover after fault condition removed			
	Over Load	≤120% Hiccup mode, recovers automatically after fault condition is removed			
	Over temperature	Shell surface temp.100°C±10°C shut down o/p voltage,automatically recover after the temperature drops.			
Environment	Working TEMP.	-40~+60°C (see below derating curve)			
	Working Humidity	20 - 95%RH non-condensing			
	Storage TEM.,Humidity	-40 - +80°C,10 - 95% RH non-condensing			
	TEMP.coefficient	±0.03%/°C(0 - 50°C)			
	Vibration	10~500Hz, 5G 12min./1 cycle, period for 72min. each along X,Y,Z axes			
Safety & EMC	Safety standards	EN61347-1 EN61347-2-13 (EU)			
	Withstand voltage	I/P-O/P:3.75KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC (EU)			
	Isolation resistance	I/P-O/P:100MΩ / 500VDC / 25°C / 70%RH			
	EMC Emission	EN55015 EN61000-3-2 EN61000-3-3 (EU)			
Others	Net Weight	1.45Kg			
	Dimension	256*78*47mm(L*W*H)			
	Packing	340*280*185mm 10pcs /CTN			
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input,rated load and 25°Cof ambient temperature. 2. Tolerance: includes set up tolerance and load regulation .				

Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W

Efficiency Curve (efficiency vs output load)






Derating Curve (output load vs TEMP.)



1. To extend their life, please refer to the Derating Curve and derate according to the temperature.
2. Please note that the rise in temperature of LED fixtures over a long period of time will cause their power to rise. Therefore, we recommend the power supply to reserve a certain amount of load to avoid overloading.


Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W

Power Factor Curve




Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W

Mechanical Specification



12V Version

Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W



24V&48V Version

- Input cable 3C*1.0mm², the Green cable to (FG), Brown cable to L, and Blue cable to N of Mains AC.
- Output cable 2C*1.5mm², Red cable (+) to LED Positive side (+), Black cable (-) to LED Negative side (-).
Two groups of 12V, One group of 24V&48V.
- Please make sure you connect these correctly otherwise your product will not function correctly and could be damaged.

Warm tips:

- Any other requests for, we can customized.

Have any questions? Please contact UK LED Lights - we're happy to help.
Please visit our website or contact us for more information.

Phase cut /Triac dimmable driver-PWM output Dimmable LED driver 200W
